



Socket CL3000, CL6000, CL9000 ASME B16.11

A105/ A105 M-87a; A350/ A350 M-89a LF1; A350/ A350 M-89a LF2;
A182/ A182 M008a F5; A182/ A182 M08a F11- CL2;
A182/ A182 M-08a F22-CL3; A182/ A182 M08a F9;
A82/ A182 M08a F91; A350/ A350 M089a LF3

SOCKOLET CL3000								
DN	sockolet redukcyjny					sockolet wyk normalne		
	A		B		waga	C*		waga
	mm	cal	mm	cal	kg	mm	cal	kg
1/8"	19.00	3/4"	16.00	5/8"	0.06			
1/4"	19.00	3/4"	16.00	5/8"	0.06			
3/8"	20.50	13/16"	19.00	3/4"	0.09			
1/2"	25.50	1"	24.00	15/16"	0.11	14.00	9/16"	0.12
3/4"	27.00	1 1/16	30.00	1 3/16	0.17	19.00	3/4"	0.19
1"	33.50	1 5/16	36.50	1 7/16	0.29	24.00	15/16"	0.31
1 1/4"	33.50	1 5/16	44.50	1 3/4	0.41	32.00	1 1/4	0.45
1 1/2"	35.00	1 3/8	51.00	2"	0.46	38.00	1 1/2	0.50
2"	38.00	1 1/2	65.00	2 9/16	0.80	49.00	1 15/16	0.87
2 1/2"	46.00	1 13/16	76.00	3"	1.40	59.00	2 5/16	1.50
3"	51.00	2"	93.50	3 11/16	2.00	73.50	2 7/8	2.15
3 1/2"	54.00	2 1/8	101.50	4"	2.60	85.00	3 5/16	2.80
4"	57.00	2 1/4	120.50	4 3/4	3.30	97.00	3 13/16	3.50

SOCKOLET CL6000 **					
DN	sockolet redukcyjny				
	A		B		waga
	mm	cal	mm	cal	kg
1/4"	28.50	1 1/8	14.00	9/16"	0.20
3/8"	28.50	1 1/8	14.00	9/16"	0.20
1/2"	31.50	1 1/4	19.00	3/4"	0.30
3/4"	36.50	1 7/16	25.50	1"	0.50
1"	39.50	1 9/16	33.50	1 5/16	0.90
1 1/4"	39.50	1 9/16	38.00	1 1/2	0.85
1 1/2"	43.00	1 11/16	49.00	1 15/16	1.45
2"	52.50	2 1/6	59.00	2 5/16	2.75

SOCKOLET CL9000 ***					
DN	sockolet redukcyjny				
	A		B		waga
	mm	cal	mm	cal	kg
1/2"	31.50	1 1/4	19.00	3/4"	0.32
3/4"	36.50	1 7/16	25.50	1"	0.55
1"	39.50	1 9/16	33.50	1 5/16	0.95
1 1/2"	43.00	1 11/16	49.00	1 15/16	1.50
2"	52.50	2 1/6	59.00	2 5/16	2.90

Uwagi:

* - sockolety przeznaczone dla rur STD oraz XS

** - sockolety przeznaczone dla rur SCH160

*** - sockolety przeznaczone dla rur XXS